

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1683	(pinion or gear) near50 valve and valve near30 rotat\$4 and engine near50 intake near50 exhaust	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 09:37
L2	17536	(resilien\$4 or flexible or rubber or elastic\$4) near50 (torque or vibrat\$5) near50 (gear or shaft)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:39
L3	16	1 and 2	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 09:40
L4	12654	(resilien\$4 or flexible or rubber or elastic\$4) near50 (gear or shaft) near50 (pinion or worm or bevel)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:02
L5	197410	("123").CLAS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/02/08 10:03
L6	237419	("74").CLAS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/02/08 10:03
L7	177	4 and 5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:08
L8	29519	("464").CLAS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/02/08 10:08
L9	1730	(5 or 6 or 8) and ((torsion\$3 or torque or vibrat\$4 or shock or friction\$3) near40 gear near40 (resilient\$4 or flexible or rubber or elastic\$5))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:40
L10	1447	(5 or 6 or 8) and ((torsion\$3 or torque or vibrat\$4 or shock or friction\$3) near40 gear near40 (damper or damping or dampening or dampen or absorb\$3 or resilient\$4 or flexible or rubber or elastic\$5)) near70 (hub or shaft)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:28

L11	331	10 and (gear near10 (bevel or worm))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:14
L12	322	11 not 7	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:26
L13	3530	(123/80r,80ba,80bb,80c,80d,80da,190.1,190.12,190.3,190.4,190.5,190.6,190.7,190.8,190.9,190.11,190.14,190.15,190.2). CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/02/08 10:28
L14	5200	((torsion\$3 or torque or vibrat\$4 or shock or friction\$3) near40 (pinion or gear) near40 (damper or damping or dampening or dampen or absorb\$3 or resilient\$4 or flexible or rubber or elastic\$5)) near70 (hub or shaft)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:29
L15	2	(13 and 14) not 12	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:33
L16	148	(gear near5 (bevel or worm)) and 13	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:34
L17	60831	((torsion\$3 or torque or vibrat\$4 or shock or friction\$3) near "30" gear near30 (resilient\$4 or flexible or rubber or elastic\$5))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:41
L18	20199	((torsion\$3 or torque or vibrat\$4 or shock or friction\$3) near "30" gear near30 (resilient\$4 or flexible or rubber or elastic\$5)) near30 (hub or shaft)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 10:41
L19	784	8 and 18	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 11:14
L20	377	(backlash or (back adj lash)) near20 gear near40 (elastic\$6 or rubber\$4 or flexible) near50 gear	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 11:15
L21	81	(6 and 20) not 19	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 11:28

L22	1497	(74/411,461).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/02/08 11:28
L23	1435	22 not (3 or 7 or 12 or 16 or 21)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 11:29
L24	312	23 and (gear or sprocket) near30 (rubber\$4 or elastic\$4 or elastomer\$4 or resilient)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/08 11:32